

Package: emaki (via r-universe)

October 16, 2026

Type Package

Title Generate 'Seedance' Videos and Images with 'emaki'

Version 0.1.0

Description Official SDK for 'emaki' <<https://emaki.ai>>, the Japanese-language AI video generator for 'Seedance' 2.5 and 'Seedance' 2.0. Submit text-to-video, image-to-video and image runs with your 'emaki' API key, wait for the result URL, and check your remaining credits.

License MIT + file LICENSE

URL https://emaki.ai/?utm_source=r-universe&utm_medium=package,
<https://emaki.ai/seedance-2-5>,
<https://github.com/hanshs474/emaki-r>

BugReports <https://github.com/hanshs474/emaki-r/issues>

Imports curl, jsonlite

Encoding UTF-8

Config/pak/sysreqs libssl-dev

Repository <https://hanshs474.r-universe.dev>

Date/Publication 2026-10-16 04:34:51 UTC

RemoteUrl <https://github.com/hanshs474/emaki-r>

RemoteRef HEAD

RemoteSha 2745714846a07dc192fa90fca5de782bd5457479

Contents

emaki_generate_video	2
emaki_submit	3

Index	4
--------------	----------

emaki_generate_video *Generate a Seedance video or an image on emaki*

Description

Submits one run on emaki (<https://emaki.ai>), waits for it and returns the result URL. Failures signal a condition of class emaki_auth, emaki_quota, emaki_plan, emaki_busy, emaki_rejected, emaki_validation, emaki_failed, emaki_timeout or emaki_other.

Usage

```
emaki_generate_video(prompt, model = "seedance_2_5", parameters = NULL, api_key = NULL,
  poll_seconds = 5, timeout_seconds = 900, post = emaki_post)
emaki_generate_image(prompt, model = "nano_banana_2_lite", parameters = NULL, api_key = NULL,
  poll_seconds = 5, timeout_seconds = 900, post = emaki_post)
```

Arguments

prompt	What to generate. For image to video, the motion.
model	Model id: "seedance_2_5", "seedance_2", "seedance_2_fast", "seedance_2_mini", "minimax_h3", "veo_3_1"; images "nano_banana_2_lite", "nano_banana_2", "seedream_5_lite", "gpt_image_2".
parameters	A named list passed through as-is, e.g. <code>list(duration = 8, resolution = "720p", aspect_ratio = "9:16", image = "https://...")</code> .
api_key	Key from https://emaki.ai/settings/apikeys ; defaults to the EMAKI_API_KEY environment variable.
poll_seconds	How often the run is polled.
timeout_seconds	Deadline for the whole call.
post	The HTTP function; replaceable in tests.

Value

The URL of the finished file.

Examples

```
## Not run:
emaki_generate_video("a paper lantern drifting down a night river",
  parameters = list(duration = 8, resolution = "720p"))
emaki_generate_image("a ramen stall in the rain, neon reflections")

## End(Not run)
```

emaki_submit*Submit a run, look it up, read your credits*

Description

Lower-level calls for submitting now and collecting later.

Usage

```
emaki_submit(prompt, model = "seedance_2_5", parameters = NULL, api_key = NULL, post = emaki_post)
emaki_status(id, api_key = NULL, post = emaki_post)
emaki_credits(api_key = NULL, post = emaki_post)
```

Arguments

prompt	What to generate.
model	Model id, as in emaki_generate_video .
parameters	A named list passed through as-is.
id	The id returned by emaki_submit.
api_key	Key from https://emaki.ai/settings/apikeys ; defaults to EMAKI_API_KEY.
post	The HTTP function; replaceable in tests.

Value

emaki_submit: the run id. emaki_status: a list with id, status ("generating", "completed" or "failed"), videoUrl and failureCode. emaki_credits: remaining credits as an integer (free to call).

Examples

```
## Not run:
id <- emaki_submit("a fox trotting through fresh snow")
emaki_status(id)$status
emaki_credits()

## End(Not run)
```

Index

emaki_credits (emaki_submit), [3](#)
emaki_generate_image
 (emaki_generate_video), [2](#)
emaki_generate_video, [2](#), [3](#)
emaki_status (emaki_submit), [3](#)
emaki_submit, [3](#)